WO 2005/057728 PCT/NL2004/000860

AMENDED CLAIMS

[Received by the International Bureau on 14 June 2005 (14.06.05): original claims 1-9 amended (2 pages)]

CLAIMS

- 1. Device comprising a patch antenna (6), and coupling means for connecting the antenna to an electronic component (5), wherein the patch antenna is arranged on one side of an antenna plate (1), characterized in that the electronic component can be mounted on the other side of the antenna plate (1) and that the coupling means comprise a metal passage (2) through the antenna plate which transposes into a bond pad (8) against the antenna plate on the other side, and a metal bond wire (3) between the electronic component and the bond pad (8), wherein the length of the passage, as seen perpendicularly of the antenna plate, is smaller than a quarter-wavelength of a signal to be processed by the antenna.
 - 2. Device as claimed in claim 1, characterized in that the length of the bond wire is smaller than a quarter-wavelength of a signal to be processed by the antenna.
- 3. Device as claimed in either of the foregoing claims,
 20 characterized in that an electrically conductive plate for
 the patch antenna is arranged against the antenna plate at
 the side of the electronic component, which electrically
 conductive plate is provided with a recess for the passage.
- Device as claimed in any of the foregoing claims,
 characterized in that the electronic component is an amplifier, such as a low noise amplifier.
 - 5. Device as claimed in any of the foregoing claims, characterized in that on the side of the electronic component the passage transposes into a bond pad for the bond wire.
 - 6. Device as claimed in any of the foregoing claims, characterized in that the passage has a substantially cylindrical form.

30

7. Device as claimed in any of the foregoing claims,

WO 2005/057728 PCT/NL2004/000860

characterized in that on the side of the antenna the passage makes direct contact with a power supply line of the patch antenna.

- 8. Device as claimed in claim 7, characterized in that
 the periphery of the passage substantially corresponds with
 the width of the power supply line.
 - 9. Radar receiver provided with a device as claimed in any of the foregoing claims.